
# 18V LXT® LITHIUM-ION CORDLESS 16 GAUGE NIBBLER

#### HIGH CAPACITY, CONVENIENT AND POWERFUL

- Makita-built Motor Delivers 1,900 SPM for Fast and Smooth Cutting
- Ideal for Cutting Roofing Sheet Metal at Thicknesses Up to 16 Gauge
- Die Holder Rotates 360° for Increased Versatility
- Convenient Chip Disposal is Below Cutting Material to Minimize Damage to **Cutting Surface**
- Compact Cutting Radius (1-3/4" Inner Edge, 2" Outer Edge) for Precision **Applications**



**POWER** 







## PERFORMANCE & VERSATILITY.

18V LXT® LITHIUM-ION CORDLESS 16 GA. NIBBLER

### **Model LXNJ01/Z**

#### **FEATURES & BENEFITS**

- Makita-built motor delivers 1,900 SPM for fast and smooth cutting
- Ideal for cutting roofing sheet metal at thicknesses up to 16 gauge
- Die holder rotates 360° for increased versatility
- Convenient chip disposal is below cutting material to minimize damage to cutting surface
- Compact cutting radius (1-3/4" inner edge, 2" outer edge) for precision applications
- Battery capacity warning system turns on indicator light and automatically stops motor to notify user when it is time to recharge the battery
- Lock-on sliding switch for continuous operation
- Anti-restart feature prevents motor start-up when battery is inserted with switch locked on
- Rubberized soft grip for improved comfort and control
- Built-in thickness gauge for convenience
- Externally accessible carbon brushes for greater serviceability
- LXT° Lithium-lon battery provides longer run time, 5x lower self-discharge (for use any time) and 16 firm holding contact terminals (for constant high power)
- 30-Minute Rapid Optimum Charger communicates with the battery's built-in chip throughout the charging process to optimize battery life by actively controlling current, voltage and temperature

#### STANDARD EQUIPMENT

- 2 ea. 18V LXT° Lithium-Ion Battery (BL1830)
- 30-Minute Rapid Optimum Charger (DC18RA)
- Tool Bag (821016-X)
- Wrench (781028-4)
- LXNJ01Z Tool Only (batteries, charger and tool bag not included)







Model LXNJ01Z



#### **SPECIFICATIONS**

	<i>!</i>	
Capacity:	Mild Steel Stainless Steel Aluminum	16 ga.   1.6 mm 18 ga.   1.2 mm 12 ga.   2.5 mm
No load speed		0-1,900 SPM
Min. cutting radius Min. cutting radius		(Inside Edge) 1-3/4" (Outside Edge) 2"
Battery		18V LXT® Lithium-lon
Overall length		12-3/8"
Net Weight		4.8 lbs. (w/battery)
UPC code:	LXNJ01 LXNJ01Z	088381-636926 088381-636933

#### **OPTIONAL ACCESSORIES**

Punch (A-83951)

Die (A-15051)





Makita offers a wide variety of CORDLESS accessories. For a complete listing, please refer to the Makita General Catalog or visit our website at **makitatools.com**, or call **1-800-4MAKITA**.